

# Sakura Air Conditioner User-friendly, Earth-friendly



SPW-32RA



SPW-29RA



Packaged Wall Through A/C  
(Twin Ducted Wall Mounted Type)

## Packaged Wall Through A/C

(Twin Ducted Wall Mounted Type)

### Specifications

Model		SPW-32RA	SPW-29RA
Cooling Capacity	kW	3.2	2.9
	btu/hr	11,000	
Heating Capacity	kW	3.2	2.8
	btu/hr	11,000	
Thermostatic Control		yes	yes
Fan Speed Settings (Fan Only Setting)		3	
Control Panel		Remote Only	Electronic
Remote Control		yes	yes
Timer		24	24
Dehumidifying Capacity	liters/day max	21.6	21.6
Continuous Drain Outlet		yes	yes
Airflow Volume	m <sup>3</sup> /h max	400	400
Operating Temperature	°C	Cool 18 to 43 Heat -5 to 24	Cool 18 to 43
Oscillating louvres		yes	-
Exhaust hose size (diameter)	mm	intake 150 / outlet 160	
Wall kit supplied		yes	
Noise Level	dB(A)	50	38-45
Refrigerant Charge	Gas/g	R410A / 520	R410A
Energy Efficiency Rating (EER) cool/heat		A	
Input Power: Cooling	W	1,220	1,090
Input Power: Heating	W	1,090	960
Voltage	V	220-240	220-240
Frequency	Hz	50	50
Net Weight	kg	42	42
Gross Weight	kg	44	44
Product Dimensions (HxWxD)	mm	550X930X260	550X930X260
Box Dimensions (HxWxD)	mm	670x1160x320	